# Hiding an elephant into a matchbox with transformation optics

M. R. Forouzeshfard <sup>a,b</sup>, T. Tyc <sup>b</sup>, and M. Hosseini Farzad <sup>a</sup>

 <sup>a</sup> Department of Physics, College of Science, Shiraz University, Shiraz 71454, Iran
 <sup>b</sup> Institute of Theoretical Physics and Astrophysics, Masaryk University, 61137 Brno, Czech Republic

ABSTRACT—Based on transformation optics, we propose an illusion device that can make objects look much smaller and different than they actually are. In particular, the device has a capability to hide a large object (like an elephant) into a small one (like a matchbox). Compared to previous proposals for illusion devices, there is no requirement for negative refractive index or for speed of light going to infinity as in Euclidean invisible cloaks. We demonstrate the of the device by full wave functionality simulations.

**KEYWORDS:** Invisibility Cloak, Illusion Optics, Metamaterials, Transformation Optics

# **I.INTRODUCTION**

Transformation optics (TO) [1]- [4] is a rapidly evolving field of optics that has led to designing many novel and fascinating devices, as well as constructing some of them experimentally employing metamaterials [5]. Invisibility cloak is the most prominent example of a device based on TO. Two archetypes of invisibility cloak were proposed simultaneously by Leonhardt [1] and Pendry et. al. [2] to create a hollow region in space such that an object which is inserted in this region is hidden from an outside observer. Both of these cloaks contained zeroes of the refractive index, which makes it difficult to realize experimentally [6] and impossible in principle to work broadband [4]. This problem was eliminated by employing non-Euclidean geometry in designing the cloak [7]. Another strategy is to relax the demand of omnidirectional functionality, which led to designing a so-called carpet cloak [8]. Cloak at a distance or external cloak is another type of cloak which uses TO for hiding an object which

is placed outside a negative index shell of the cloak [9]. This device uses folded geometry and negative index materials for creating the invisibility effect [10].

One can also use the properties of an external cloak to create an illusion device [9]. In the illusion devices, one object is hidden from the sight of the observer and another object (with different shape and material properties) is seen by the observer instead of the first object. Further illusion devices are described in [12, 13, 14, 15]. TO has been used for designing also other devices such as concentrators [16], rotators [17] and superscatterers [18].

In this paper we use TO for designing a new type of an illusion device. With this device one can make a large object to appear much smaller and of a different shape, almost "like hiding an elephant into a matchbox". Our device works in a relatively simple way and its advantage is that it does not employ the negative refractive index like other illusion devices, and also the refractive index is not zero, so its functionality does not have to rely on resonant effects as in the Euclidean invisibility cloak.

The paper is organized as follows. In Sec. 2 we describe our device, in Sec. 3 we present the results of numerical simulations and we present our conclusions in Sec. 4.

# **II.** THE ILLUSION DEVICE

According to the theory of TO, there are two spaces: virtual space where refractive index is unity and physical space with a non-unit index, and there is a particular geometrical mapping between the two spaces. If we denote the Cartesian coordinates in virtual space and physical space by  $(x'_0, y'_0, z'_0)$  and  $(x_0, y_0, z_0)$ , respectively, then the relation between electromagnetic parameters of the two spaces are as follows [2, 4]:

$$\varepsilon = \frac{\Lambda \varepsilon' \Lambda^T}{\det \Lambda}, \qquad \mu = \frac{\Lambda \mu' \Lambda^T}{\det \Lambda}$$
(1)

where in  $\varepsilon(\varepsilon')$  and  $\mu(\mu')$  denote permittivity and permeability tensors in physical (virtual) space and  $\Lambda_{ij} = \partial x'_i / \partial x_j$ .

We now employ the following transformation in the cylindrical coordinate system:  $r = f(r'), \theta = \theta', z = z'$  with the function fdefined by

$$f = \begin{cases} \left(\frac{a-b}{c-b}\right)r' + b\left(\frac{c-a}{c-b}\right)for & c \le r' \le b \\ \\ (a/c)r' & for & 0 \le r' \le c \end{cases}$$
(2)

where in f(c) = a and f(b) = b. Fig. 1 shows the graph of the above transformation.



**Fig 1.** Graph of the function f(r') in eq. (2)

The transformation matrices for the core  $(0 \le r \le a)$  and the shell  $(a \le r \le b)$  in cylindrical coordinate are as follows:

$$\mathbf{\Lambda}_{core} = \begin{pmatrix} a/c & 0 & 0\\ 0 & 1 & 0\\ 0 & 0 & 1 \end{pmatrix}, \tag{3}$$

$$\mathbf{\Lambda}_{shell} = \begin{pmatrix} \frac{(a-b)}{(c-b)} & 0 & 0\\ 0 & 1 & 0\\ 0 & 0 & 1 \end{pmatrix}.$$
(4)

Eq. (2) then yields the tensors for the core/shell of the device:

$$\varepsilon_{core} = \mu_{core} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & (c/a)^2 \end{pmatrix},$$
 (5)

$$\varepsilon_{core} = \mu_{core} = \begin{pmatrix} \left(\frac{a-b}{c-b}\right)\frac{r'}{r} & 0 & 0\\ 0 & \left(\frac{c-b}{a-b}\right)\frac{r}{r'} & 0\\ 0 & 0 & \left(\frac{c-b}{a-b}\right)\frac{r'}{r} \end{pmatrix},$$

(6)

where virtual space is supposed to be empty space with  $\varepsilon' = \mu' = 1$ .

Now suppose that  $c \ll a$ , which means that the size of the core region  $(0 \le r' \le c)$  in virtual space is much smaller than the size of the corresponding region  $(0 \le r \le a)$  in physical space. If we insert a large object into a conductor box and put this box in the core part of our illusion device, this box looks much smaller than its real physical size. This way, with a little bit of exaggeration we can say that an elephant can be hidden in a matchbox. In reality the elephant would be hidden in a box larger than the elephant, but because of the illusion, this box would look much smaller than

it would actually be. Fig. 2 (a) shows a schematic diagram of our illusion device in physical space and Fig. 2 (b) shows the observer's imagination when he/she looks at the device. Our device has an advantage over the previously reported illusion devices [11, 12]. For them, the position of the second object (which is going to be seen) is different from the position of the hidden object. In our device both of the objects are at the same place. And more importantly, the previous illusion devices employed negative refracting materials while our device does not. This is a great advantage in terms of possible experimental realization. Our device also does not require speed of light to be infinite as is the case of the Euclidean invisibility cloak.



**Fig 2.** A schematic diagram for the illusion device. a) Physical space: a large object (elephant) is inserted in a box and the box is placed in the core of the device. b) Virtual space: the observer sees a box (matchbox) that is much smaller than the real box in physical space and the object inside. The object is not visible.

#### **III.**NUMERICAL SIMULATION

In order to simulate wave propagation in the illusion device, we first calculate the Cartesian elements of the permittivity tensor from the above cylindrical elements by the relations [5]

$$\varepsilon_{xx} = \varepsilon_r \cos^2 \theta + \varepsilon_\theta \sin^2 \theta,$$
  

$$\varepsilon_{xy} = \varepsilon_{yx} = (\varepsilon_r - \varepsilon_\theta) \cos \theta \sin \theta,$$
  

$$\varepsilon_{yy} = \varepsilon_r \sin^2 \theta + \varepsilon_\theta \cos^2 \theta,$$
  
(7)

and similarly for  $\mu$ . Fig. 3 shows the full wave simulation (COMSOL Multiphysics) of a TE plane wave incident on this illusion device from

the left when the core region still does not contain the box.



Fig 3. Full wave simulation of the z-component of the Electric field for a TE plane wave with  $a = 2\lambda = 3$ , b = 5 and c = 0.5 incident on the empty illusion device.

Fig. 4 (a) shows the simulation for the case which the box is present in the core region, again for a TE plane wave. Fig. 4 (b) shows the corresponding field pattern in virtual space. Figs. 4 (c) and (d) show similar patterns for illumination by a point source placed at (-5,5). The parameters  $a = 2\lambda = 3, b = 5$  and c = 0.5 were used. By comparing Figs. 4 (a) and (b) or Figs. 4 (c) and (d), we see that the scattering pattern of the large box in physical space is equivalent to scattering on a much smaller box in empty space, which demonstrates the functionality of our device.

## **IV.**CONCLUSION

We have introduced a new illusion device that could hide a large object into an apparently much smaller box. We used the concept of transformation optics for designing the device and calculating the geometric and dielectric properties of the device. The operation of the device was demonstrated by wave simulations in 2D. Our device can be generalized to other shapes and coordinate systems. This illusion device can provide a similar effect to the device reported in [11], but, in contrast, it is built from realizable positive index metamaterials and also does not require singularities in its material parameters so the speed of light need not to go to infinity.



**Fig 4.** (a) Scattering pattern for a TE plane wave with  $a = 2\lambda = 3, b = 5$  and c = 0.5 unit incident from the left on the illusion device with a PEC square box with side length 4 in its core; an object (elephant) is also placed inside the box. The circles mark the boundary of the device at r = b and the boundary of the core at r = a. (b) The equivalent virtual space with a much smaller PEC box which is a coordinate transform of the box in (a). The inner circle r' = c is much smaller than the corresponding one in (a). (c) and (d) show the same, but for illumination by a point source located at (-5,5) instead of the plane wave.

### ACKNOWLEDGMENT

TT acknowledges support from grant no. P201/12/G028 of the Grant Agency of the Czech Republic.

#### REFERENCES

- [1] U. Leonhardt, "Optical Conformal Mapping," Science 312, 1777, 2006.
- [2] J. B. Pendry, D. Schuring and D. R. Smith., "Controlling Electromagnetic Fields," Science 312, 1780, 2006.
- [3] H. Y. Chen, C. T. Chan and P. Sheng, "Transformation optics and metamaterials," Nature materials, 9, 387, 2010.
- [4] U.Leonhardt and T. G. Philbin., "Transformation Optics and the Geometry of Light" Progress in Optics, 53, 69, 2009.
- [5] W. Cai and V. Shalaev, *Optical Metamaterials Fundamentals and Application*. London:

Springer New York Dordrecht Heidelberg, p 157, 2010.

- [6] D. Schurig, J. J. Mock, B. J. Justice, S. A. Cummer, J. B. Pendry, A. F. Starr, D. R. Smith, "Metamaterial electromagnetic cloak at microwave frequencies." Science, 314, 977, 2006.
- [7] U. Leonhardt and T. Tyc., "Non-Euclidean cloaking for light waves," Science, 323, 110, 2009.
- [8] J. Li and J. B. Pendry, "Hiding under the carpet: a new strategy for cloaking," Phys. Rev. Lett. 101, 203901, 2008.
- [9] Y. Lai, H. Chen, Z. Q. Zhang and C. T. Chan. "Complementary media invisibility cloak that cloaks objects at a distance outside the cloaking shell.," Phys. Rev. Lett. 102, 093901, 2009.
- [10] S. A. Ramakrishna., "Physics of negative refractive index materials" Rep. Prog. Phys. 68, 449-521, 2005.
- [11] Y. Lai, J. Ng, H. Chen, H. Dezhuan, X. JunJun, Z. Q. Zhang and C. T. Chan. "Illusion optics: The optical transformation of an object into another object," Phys. Rev. Lett. 102, 253902, 2009.
- [12] W. X. Jiang, H. F. Ma, Q. Cheng and T. J. Cui. "Illusion media: Generating virtual objects using realizable metamaterials," Appl. Phys. Lett. 96, 121910, 2010.
- [13] H. H. Zheng, J. J. Xiao, Y. Lai, C. T. Chan. "Exterior optical cloaking and illusions by using active sources: A boundary element perspective " Phys. Rev. B 81, 195116, 2010.
- [14] E. Cojocaru. "Illusion Devices with Internal or External Circular Objects Designed by the Coordinate Transformation Method," J. of Electromagn. Waves and Appl., Vol. 24, 23092317, 2010.
- [15] Z. Li, X. F. Zang, B. Cai, C. Shi and Y. M. Zhu. "Cloaks and antiobject-independent illusion optics based on illusion media" Opt. Commun. 308 9599, 2013.
- [16] M. Rahm, D. Schurig, D. A. Roberts, S. A. Cummer, D. R. Smith, and J. B. Pendry. "Design of electromagnetic cloaks and concentrators using form-invariant coordinate transformations of Maxwell's equations" Photon. Nanostr. Fundam. Appl. 6, 87, 2008.

- [17] H. Y Chen and C. T. Chan. "Transformation media that rotate electromagnetic fields" Appl. Phys. Lett. 90, 241105(2007).
- [18] T. Yang, H.Y. Chen, X. Luo, and H. Ma, "Superscatterer: Enhancement of scattering with complementary media," Opt. Express, 16, 18545, 2008.



**M. R. Forouzeshfard** was born in Estahban, Fars, Iran, on September 22, 1985. He recieved his B.Sc. degree from Isfahan University, Isfahan, Iran in 2006, and his M.Sc degree from Shahid Bahounar University of Kerman, Kerman, Iran in 2009 in atomic and molecular physics. He is a Ph.D student in Shiraz University, Shiraz, Iran in the field of optics and lasers in particular on theory of invisibility cloaks and transformation optics, and simultaneously is a visiting reseacher at Masaryk University in Brno, Czech Republic.



**Tomas Tyc** was born in Brno, Czech Republic, on February 7, 1973. He received the Master's degree and the Ph.D. degree in theoretical physics from Masaryk University, Brno, in 1996 and 1999, respectively. In 2006, he obtained habilitation and in 2009 full professorship, both from Masaryk University. He was a Research Fellow at the University of Vienna (2000), Macquarie University Sydney

(2001 and 2002), the University of Calgary (2004), and the University of St. Andrews (2007 and 2008). He is currently with the Institute of Theoretical **Physics** and Astrophysics, Masaryk University. He was initially involved in correlations in free electron beams, and later, in the field of quantum optics and quantum information theory. In 2007, he focused on optics, in particular on theory of invisible cloaks and transformation optics. He is also engaged in popularizing science and performs shows on the physics of everyday life for the general public.



M. Hosseini Farzad was born in Shiraz, Fars, Iran, on September 22, 1965. He received his B.Sc. degree from Shiraz University, Shiraz, Iran in 1988, and his Master's degree in atomic physics and Ph.D. degree in nonlinear optics from Shiraz University in 1991and 1996, respectively. He is a faculty member of Physics Department of Shiraz University from 2002 until now. During this time he graduated twenty M.Sc. students in various subject in photonic such as: stimulated Brillouin scattering, Qsolid state laser. Anderson switched localization in photonic crystals, extraordinary optical transmission, nano fiber with methalic clad, carbon nano-tube saturable absorber and Plasmonics. He also graduated one Ph.D. student in area of Plasmonics on June 2013. Furthermore at the present three Ph.D. students are under supervision of him in Shiraz University in the area of Plasmonics and invisibility cloaks.